

Flushing unit Harben 8.20 pump



Offshore ATEX II3GcT3 Zone 1, Norsok Z-015

RENTAL

Specifications	
Dimension	B= 900 L=1650 H=1350
Weight	1000 kg
Lifting/Transport	Frame with pockets for forklift / "Maskindirektivet 522"
Pump	Harben 8.20
Reservoir Capacity	300 litre
Max flow 50Hz	45 ltr/min
Max pressure 50Hz	345 bar
Outlet connection	½" BSP
Return connection	¾" BSP
Outlet cooling	½" BSP
Inlet cooling	½" BSP
Filter house LP	Pall
Filter element LP	HC9020FKP4H
Filter house HP	Pall

Filter element HP	HC9020FKP4H
Equipment /functions	Flow indicator, tapping for bottle sampling, connection for inline sampling using particle monitor, selector valve and PCV
Voltage range	400 – 480 - / 660 – 690 V
Frequency	50 – 60 Hz
Current consumption	63A
Motor	WEG Industrias S. A. 30 Kw Multivoltage (380 – 690 VAC) Ex II 2 G EEx de IIB T4
Control cabinet (starter)	CEAG EEX de cabinet (modified) ATEX ZONE II 2 EEx de (ia) IIC T6
Year of construction	2005

ingenious simplicity

info@proserv.com
www.proserv.com

proserv