

Electric driven hydraulics unit



Electric driven hydraulic unit HA05

NORSOK Standard Z-015, Temporary Equipment
 Hazardous Area – Zone 1, DNV Certification 2.7.1

Specifications HA05	
Pump	Electric driven
Length	1400 mm
Width	1300 mm
Height	2100 mm
Weight	Tara: 1250kg Max gross weight: 1500kg
Centre forks pockets	1,22 m
Forks pockets width	0,24 m
High pressure pump	Dension Hydraulics double wing pump T7BBS-B06-B02-R00
Electric Motor	Bartec Varnost EExde, 18,5Kw, 400/690V 50/60 Hz
Voltage	Hazardous Area – Zone 1 60 Hz 400-690V / 35Amps – 21Amps
Cert nr	Ptb nr EX-96.0.1051
Pump	Dension Hydraulics
Model	T7BBS B06 B02 1R00 A1
Code	N00-00764-0-0
Fluid/tank	Hydraulics oil/100 litre
Return filter	HC9100 FKP8H
Pressure valve	OIS B-10-2-8B
Flow valve	OIS OM320370030000A
Rec. working pressure	200 bar
Max discharge pressure	200 bar
Max flow rate	8 + 32 total 40 litres/min @200 bar
Connection pressure	5020RW
Connection return	5011RW
Connection leak	5011RW
Utilities required	Fresh water for cooling supply

ingenious simplicity

info@proserv.com
 www.proserv.com

